Manufacturer/Distributor: Litrox Factory Investments LLC (443960-91)

Material Safety Data Sheet

XTREME CLEAR GEL

Page 1 of 6

Section 1 – Identification

Product Name: XTREME CLEAR GEL

Chemical Name: N/A US 8130 SW Portland, Oregon, Beaverton-Hillsdale Highway 97225.

Family: UV GELS
Product Use: NAIL GEL
Product #: 4020141

Section 2 - Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

• May be slightly toxic.

• May cause moderate skin injury (reddening & swelling).

• May cause eye irritation.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry No specific information available.

Eye No specific information available. Contains materials that are essentially nonirritating, but contact

may cause slight transient irritation.

Skin No specific information available. Contains materials that may cause moderate skin injury (reddening

and swelling) and/or sensitization. Prolonged contact may cause blister formation (burns). Since

irritation may not occur immediately, contact can go unnoticed.

Ingestion No specific information available. Contains materials that are considered to be practically nontoxic.

Inhalation No specific information available. Low volatility makes vapor inhalation unlikely. Aerosol can be

irritating.

Sub-Chronic Effects No specific information available. Limited tests showed no evidence of teratogenicity in animals. A

lifetime skin painting study with mice showed no evidence of carcinogenicity.

NOTE: Refer to Section 11, Toxicological Information for Details

Section 3 - Composition/Information on Ingredients

Chemical Identity	CAS Numbers	EINECS#	INCI Name	Exposure	Limits	Carcinogen	%
				OSHA TWA/STEL	ACGIH TWA/STEL	IARC/NTP/OSHA	
Polyurethane Acrylate Oligomer	Exempt N	/E	Di-Hema Trimethylhexyl Dicarbamate*	N/E N/E		Not Listed	80-90
Isobornyl Methacrylate	7534-94-3	231-403-1	Isobornyl Methacrylate	N/E	N/E	Not Listed	5-15
Hydroxycyclohexyl phenyl ketone	947-19-3 2	13-426-9	Hydroxycyclohexyl phenyl ketone	N/E N/E		Not Listed	0-2
D&C Violet #2	81-48-1	201-353-5	CI60725	N/E	N/E	Not Listed	0-0.5
N/E - None Established N/R - Not Reviewed	N/DA - No Data N/A - Not Appli		* See section 16				

Polyurethane Acrylate Oligomer: Hazard Symbol: Xi Risk Phrases: R36/37/38 Safety Phrases: S14, S3/7, S62

 Isobomyl Methacrylate:
 Hazard Symbol – Xi
 Risk Phrases – R36/37/38
 Safety Phrases – S26, S27, S28, S29, S30, S33, S35, S36

Hydroxycyclohexyl Phenyl Ketone: Hazard Symbol: Xi Risk Phrases: R36, R37, R38 Safety Phrases: S26, S37

See Section 16 for Risk and Safety Phrase Key

Section 4 - First Aid Measures

First Aid for Eye Flush eyes with water for 15 minutes, including under eyelids. If irritation continues, seek medical

attention.

First Aid for Skin Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

First Aid for Inhalation In case of exposure to a high concentration of vapor or mist, remove person to fresh air. If breathing

has stopped, administer artificial respiration and seek medical attention.

First Aid for Ingestion If appreciable quantities are swallowed, seek medical attention.

MSDS#: KIG020808-XCG

Material Safety Data Sheet

XTREME CLEAR GEL

Page 2 of 6

Section 5 - Fire Fighting Measures

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
>212 °F/100 °C Setaflash	No Data	No Data

Method:

Extinguishing Media: Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

Fire Fighting Remove all ignition sources. Wear self-contained breathing apparatus and complete personal Instructions: protective equipment when entering confined areas where potential for exposure to vapors or

products of combustion exists.

Unusual Hazards: High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can

result in explosions and the violent rupture of storage vessels or containers. Avoid the use of a

stream of water to control fires since frothing can occur.

Section 6 - Accidental Release Measures

Spill or Release Procedures - Spontaneous polymerization can occur. Although material is non-flammable please try to eliminate all ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Dike and recover large spills. Soak up small spills with inert solids (such as vermiculite, clay) and sweep/shovel into disposal container. Wash spill area with strong detregent and water solution; rinse with water, but minimize water use during cleanup. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

Section 7 - Handling and Storage

Handling Avoid contact with skin and eyes. Avoid breathing vapor. Keep container closed when not in use. Avoid

prolonged exposure to light. Remove all contaminated clothing, shoes, belts and other leather goods

immediately. Incinerate leather goods (including shoes). Wash contaminated clothing thoroughly before reuse. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of

increased penetration potential.

When handling gel for product use, do not heat above 100°F/38°C or disassociation of resins in product may

occur. Material is UV light sensitive, avoid prolonged exposure to light/heat.

Storage Store in a cool place, away from heat and light. Store at temperatures below 100°F/38°C.

Explosion Hazard High temperatures and fire conditions may cause rapid and uncontrolled polymerization which can result in

explosions and the violent rupture of storage vessels or containers.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls Local exhaust recommended to control exposure which may result from operations generating aerosols and

hot operations generating vapors.

PERSONAL PROTECTIVE EOUIPMENT

General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a

hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves,

apron, boots, or whole body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection Chemical splash goggles.
Skin Protection Impervious gloves (Neoprene).

Respiratory Protection A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be

permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by nuisance level organic vapor dust masks can be used, however the

use of the respirator is limited. Follow OSHA respirator regulations found in 29 CFR 1910.134 or

European Standard EN 149.

Material Safety Data Sheet

XTREME CLEAR GEL

Page 3 of 6

Section 9 - Physical and Chemical Properties

Appearance	Odor & Odor Threshold	$_{ m P}{ m H}$	Specific Gravity	Viscosity	% Volatile
Clear, viscous liquid	characteristic acrylate odor	NA	(H2O=1): 1.15	N/DA	By Volume: < 0.5

Boiling Point/ Freezing Point	Decomposition Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
N/A	N/A	N/A	(mm Hg) @ 20 C:< 0.01	No Data	No Data	No Data	Insoluble

Flash Point(°F/°C)	Flammable Limit(vol%)	Auto-ignition Temperature(vol%)
>212 °F/100 °C Setaflash	No Data	No Data

Section 10 - Stability and Reactivity

Stability

Normally Stable

Hazardous Decomposition Products:

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide.

Incompatibility (Materials to Avoid):

Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and string bases.

Hazardous Polymerization:

May occur -- Uncontrolled polymerization may cause rapid evolution of

Heat and increased pressure that could result in violent rupture of sealed storage vessels or containers.

Conditions to Avoid:

Storage >100°F/38°C, exposure to light, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.

Section 11 - Toxicological Information

Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye	
No information available	No information available	No information available	No information available	No information	
				available	
Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers.					
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.					

Sensitization	Mutagenicity	Sub-chronic Toxicity	
No information available	No information available	No information available	

Section 12 - Ecological Information

Ecotoxicological Information

Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
N/DA N/DA		N/DA	N/DA	N/DA

Chemical Fate Information

enemical rate information	
Biodegradability	N/DA
Chemical Oxygen Demand	N/DA

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13 - Disposal Considerations

Non-contaminated, properly inhibited product is not a RCRA hazardous waste. It is the genrators responsibility to determine what is classified as a hazardous waste. Comply with all federal, state, and local regulations.

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate.

Material Safety Data Sheet

XTREME CLEAR GEL

Page 4 of 6

Section 14 - Transport Information

DOT (49 CFR 172)	
Proper Shipping Name:	Non-Regulated Material
Identification Number:	N/A
Marine Pollutant:	No
Special Provisions:	None
Emergency Response Guidebook (ERG) #:	N/A
IATA (DGR):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Packaging Instructions:	None
Emergency Response Guidance (ICAO)#:	N/A
IMO (IMDG):	
Proper Shipping Name:	Non-Regulated Material
Class or Division:	N/A
UN or ID Number:	N/A
Special Provisions & Stowage/Segregation: None	
Emergency Schedule (EmS)#:	N/A
Other Information:	Flash point >100°C

Section 15 - Regulatory Information

US Federal Regulations					
Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP), as defined by the U. S. Clean Air Act: NONE This product contains no ODS's				
Clean Water Act: Priority Pollutant	This product contains no chemicals listed under the U. S. Clean Water Act Priority Pollutant List.				
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.				
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard				
RCRA	This product is not considered to be a hazardous waste under RCRA (40 CFR 261).				
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances that carry a TPQ.				
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 304 as extremely hazardous chemical for emergency release notification ("CERCLA" List).				
SARA Title III: Section 311-312:	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: • Immediate (acute) health hazard • Delayed (chronic) health hazard • Reactive hazard				
SARA Title III: Section 313:	This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.				
TSCA Section 8(b): Inventory: This product contains chemicals listed on the TSCA inventory or otherw TSCA premanufacture notification requirements.					
TSCA Significant New Use Rule:	None of the chemicals listed have a SNUR under TSCA.				

Material Safety Data Sheet

XTREME CLEAR GEL

Page 5 of 6

State Regulations

CA Right-to-Know Law:	NONE
California No Significant Risk Rule:	NONE
MA Right-to-Know Law:	NONE
NJ Right-to-Know Law:	NONE
PA Right-to-Know Law:	NONE
FL Right-to-Know Law:	NONE
MN Right-to-Know Law	NONE

International Regulations

CDSL: Canadian Inventory	Hydroxycyclohexyl phenyl ketone CAS # 947-19-3 is on the DSL list. WHMIS = n/da
(on Canadian Transitional List)	Isobornyl Methacrylate CAS # 7534-94-3 is on the DSL list. WHMIS = n/da

Labeling according to EC directives – 1999/45/EC

European Community:



Crystal Nails Xtreme Clear Gel

- HAZARD SYMBOLS: Xi: Irritant
- Risk Phrases: **R20**: Harmful by inhalation, **R43**: May cause sensitization by skin contact.
- Safety Phrases: S24/25: Avoid contact with skin and eyes, S28A: After contact with skin, wash immediately with plenty of water, S37: Wear suitable protective gloves, S45: In case of accident, or if you feel unwell, seek medical advise immediately (show the label where possible)

Section 16 – Other Information

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbol:

Xi – Irritants


Risk Phrases:

R36/37/38 Irritating to eyes, respiratory system and skin

Safety Phrases:

S3/7 Keep container tightly closed in a cool place; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S27 Take off immediately all contaminated clothing; S28 After contact with skin, wash immediately with plenty of water; S29 Do not empty into drains; S30 Never add water to this product; S33 Take precautionary measures against static discharges; S35 This material and its container must be disposed of in a safe way; S36 Wear suitable protective clothing; S37 Wear suitable gloves; S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label

Hazard Rating System (Pictograms)



MSDS#: KIG020808-XCG

Material Safety Data Sheet

XTREME CLEAR GEL

Page 6 of 6

MSDS Prepared by:	JRR
Revision History:	02/08/2008 Initial issue
	04/30/2008 Updated INCI name for Polyurethane Acrylate Oligomer. * Most Crystal Nails gels are composed of oligomers made primarily from urethane methacrylates. Crystal Nails is using the designation Di HEMA Trimethylhexyl Dicarbamate, the official INCI name of urethane dimethacyrlate, which is substantially the equivalent of Polyurethane Acrylate Oligomer.
	09/17/2008 Updated section 16
	10/22/2008 Updated format
	11/14/2008 Updated Risk and Safety Phrases
	03/18/2009 Updated to meet Globally Harmonized System requirements. Added the EU address to section 1. Switched location of section 2 with section 3. Changed the title in sections 1, 8, and 13. Moved MSDS preparation to section 16.
	07/16/2009 Added MPH-1178A designation.

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.